

Model 3280B



- 7 functions Pen-type Digital Multimeters
- Large 3-3/4 digital LCD display with Bargraph
- Full function indication
- Diode and audible continuity

### Specifications

| Function                           | Max range | Basic accuracy | 3216 | 3218  | 3219  | 3280  | 3280B | 3290  |
|------------------------------------|-----------|----------------|------|-------|-------|-------|-------|-------|
| Voltage DC                         | 600V      | ±0.8%          | *    | *     | *     | *     | *     | *     |
| Voltage AC                         | 600V      | ±1.2%          | *    | *     | *     | *     | *     | *     |
| Current DC                         |           | ±1.5%          |      | 340mA | 400mA | 200mA |       | 400mA |
| Current AC                         |           | ±2.0%          |      | 340mA | 400mA | 200mA |       | 400mA |
| Resistance                         |           | ±3.0%          | 20MΩ | 30MΩ  | 40MΩ  | 20MΩ  | 20MΩ  | 40MΩ  |
| Non-contact voltage: 50-600V       |           |                |      |       |       | *     | *     | *     |
| Continuity: <35Ω                   |           |                |      |       |       |       |       |       |
| Diode test: Test voltage max. 3.4V |           |                |      |       |       |       |       |       |

**Size(HxWxD):** 220mm x 40mm x 33mm

**Weight:** 215g

**Accessories:**

Clamshell and button battery

Model 3218



EMC & LVD

EN: 61326

EN: 61010-1,

EN: 61010-02-031

